



## Acrylic Primer

ROCATEX Acrylic Primer is a water based polymer emulsion and is designed to give maximum penetration into the substrate to enhance surface preparation for bonding when tiling or screeding

- Concrete Screeds
- Chipboard / Timber
- Plasterboard
- Asphalt / Brickwork
- Existing Tiles
- Brickwork

### DESCRIPTION

ROCATEX Acrylic Primer is a water based polymer emulsion and is designed to give maximum penetration into the substrate to enhance surface preparation for bonding when tiling or screeding.

Suitable for internal / external use and for porous and non-porous substrates including; concrete, anhydrite and cement based rendering, existing tiles, asphalt and wooden surfaces such as; chipboard, plywood and floorboards.

### SUBSTRATE PREPARATION

Substrates should be hard, sound and free from dust, oil, grease, paint, plaster, or any other contaminants that could provide a barrier to adhesion.

Preparation of the substrate by mechanical means such as scabbling is recognised as the most effective way to provide a good key. Where a substrate has been subject to chemical contamination advice as to any specific precautions must be sought.

### APPLICATION

ROCATEX Acrylic Primer should be mixed with water in proportion from 1:1 (on slightly absorbent surfaces) to 1:2 (on absorbent surfaces) or use undiluted on wooden surfaces. Particularly absorbent surfaces may require subsequent coats to prevent air rising from the substrate and effecting the final finish. The primer should be applied with a soft brush ensuring that all puddles and any ponding is brushed out prior to screeding. The primer should not be applied to substrates with a temperature of less than +5°C.

### COVERAGE

Approximately 10m<sup>2</sup> per litre neat.

Approximately 20m<sup>2</sup> per litre when mixed with 1 litre of water.

### STORAGE

Store unopened in a dry place at temperatures above +5°C. Shelf life is 18 months from date of manufacture. A small amount of liquid may form on the surface of the material, this can be readily remixed by stirring. If the container is left open for a period of time a skin will form over the material. This skin should be removed and not mixed into the product.

## ROCATEX

Rocatex Ltd  
Units 3+4 Camwal Park  
Camwal Road  
Harrogate, HG1 4PT

T: +44 (0)1423 882 990  
F: +44 (0)1423 299 040  
E: [info@rocatex.com](mailto:info@rocatex.com)  
[www.rocatex.com](http://www.rocatex.com)

## TECHNICAL DATA

Form:	Milky solution
Specific Gravity:	1.00 - 1.05
pH:	7.00 - 9.00
Flashpoint:	None
Solids Content:	>50
Application Temp. Range:	+6°C to +30°C
Service Temp. Range:	-15°C to +75°C
Durability:	Up to 15 years when used as recommended.
Shelf Life:	Up to 18 months when stored in unopened containers, under cool dry conditions. Avoid frost.
Compatibility:	Can be used in contact with most building and decorating materials but should not be used against bituminous materials.
Limitations:	Should not be used in conditions of continuous immersion, below ground level, in areas of high abrasion (e.g. floor joints).
Colour:	Yellow