



## Flexible Additive

**A ready to use flexible additive for use with cement based adhesives & grouts**

---

### DESCRIPTION

An acrylic based additive for use with ROCATEX non-flexible cement based adhesives and grouts.

The use of ROCATEX Flexible Additive improves adhesion properties and imparts flexibility in areas where slight movement and vibration can occur. ROCATEX Flexible Additive will enhance product performance for use with underfloor heating. Suitable for addition to adhesives and grouts prior to use on timber floors that first have been overlaid with at least 18mm exterior grade plywood.

### PREPARATION

This pre-diluted additive should be mixed with ROCATEX adhesives and grouts as a replacement for water.

### MIXING

#### Adhesive

Mix 20kg of ROCATEX C1F Rapid Grey adhesive in a clean mixing vessel with 4.4 litres of ROCATEX Flexible Additive until a smooth creamy consistency is achieved using a suitable drill with whisk attachment. Mix at a slow speed until a smooth, lump-free consistency is achieved.

#### Grout

Mix 10kg of ROCATEX CG2 Wide Joint Grout in a clean mixing vessel with 2.4 litres of ROCATEX Flexible Additive until a smooth creamy consistency is achieved using a suitable drill with whisk attachment. Mix at a slow speed until a smooth, lump-free consistency is achieved.

### Note

The addition of ROCATEX Flexible Additive will enhance the adhesion performance of adhesive or grout. Remove all surplus product before it can set using a damp cloth as set product will prove very difficult to remove later. Clean all tools immediately after use.

### STORAGE

Store unopened in a cool dry, frost free environment and away from direct sunlight.