



Stone & Grout Sealer

Forms a colourless barrier that helps to protect porous stone surfaces and grout joints from penetration by water, oil, dirt, grease and limescale whilst allowing surfaces to breathe.

**Travertine / Limestone / Marble / Slate
Sandstone / Terracotta / Brick / Paving
Rapid Drying / Colourless
Microporous / VOC Compliant
Internal / External**

DESCRIPTION

Forms a colourless barrier that helps to protect porous stone surfaces and grout joints from penetration by water, oil, dirt, grease and limescale whilst allowing surfaces to breathe. Suitable for artificial stone, brick, paving and limestone, marble, quarry, sandstone, slate, terracotta, terrazzo and travertine tiles. Suitable for internal and external applications.

DIRECTIONS

Always use a mask. Use in well ventilated areas. Areas to be treated must be clean, dry and free from dust. Older contaminated and dirty stone surfaces and grouting should be cleaned with a dilute solution of ROCATEX Tile & Stone Renovator 1:10. Rinse well to remove residues and leave to dry (24 hours).

Shake can well and hold 15-20cm from the surface and spray in a sweeping motion. The surface will be touch dry within 5 minutes. Test the area 30 minutes after application with a little water. If the water absorbs then a second or even a third coat may be required to obtain maximum protection. A 2-3 hour curing time is recommended upon completion before allowing traffic.

On polished stone surfaces, after 5 minutes and while the sealer is still wet, remove any visible excess sealer with an absorbent cloth. Finish after removal of excess by buffing with a soft lint free cloth or machine with buffing pad. Do not allow residues to dry on the surface.

Please note, when using as a grout protector with ceramic and porcelain tiles, ensure overspray on tiles is wiped clean whilst still wet.

This product will dry after about 2 hours, but will take a further 70 hours to become fully resistant. During this time DO NOT cover the surface and wipe up any spills immediately. For wet areas including shower enclosures and wet rooms allow the sealer to cure fully before use. Consideration should also be given to any moisture trapped in newly laid surfaces in terms of covering the surface after sealer application.

Do not apply in direct sunlight or in temperatures exceeding 25°C. Do not spray on to painted, acrylic or stained surfaces such as cabinets and stained timber skirting boards. Mask and protect these surfaces before application. Do NOT apply if an underfloor heating system is on. Use only in well ventilated areas. Without prior experience or in cases of doubt, try the product in an inconspicuous area prior to use.

ROCATEX

Rocatex Ltd
Units 3+4 Camwal Park
Camwal Road
Harrogate, HG1 4PT

T: +44 (0)1423 882 990
F: +44 (0)1423 299 040
E: info@rocatex.com
www.rocatex.com

COVERAGE

On surfaces:

Per 600ml, 5-25m depending upon the porosity and number of coats required.

On grout joints:

Per 600ml, 600 linear metres depending upon the width of the grout joint and number of coats required.

MAINTENANCE

Routinely sweep the floor and wash with ROCATEX Tile & Stone Cleaner. Clean walls and work surfaces with ROCATEX Tile & Stone Cleaner. Heavily used areas may require intense cleaning every 2-3 years and you can use ROCATEX Tile & Stone Renovator (refer to data sheet) followed by a top up coat of sealer.

STORAGE

Store in a cool, dry, frost free environment.

HEALTH & SAFETY

Extremely flammable. Irritating to skin. Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.

Keep out of reach of children. Keep away from sources of ignition. No smoking. Do not breathe vapour/spray. Avoid contact with skin and eyes. Do not empty into drains. Use only in well ventilated areas. Pressurised container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.



Use only as directed.

UN1950.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.